

Quickie® R2

The Quickie R2 Models combine a compact frame and an adjustable wheel design to offer optimum maneuverability and stability. The Quickie R2 is available in Rigid or Adjustable frame options. The Quickie R2 Rigid offers a lightweight, superior performance chair by eliminating the hardware and moving components required in an adjustable chair. The Quickie R2 Adjustable offers an adjustable seat design to accommodate the seat angle adjustments without the use of tools.



Angle-Adjustable Seat Design

The Quickie R2 Adjustable model allows you to change our back angle to one of three pre-set positions as well as set the squeeze to 2", 3" or 4" to optimize the seat position.



Front Caster Angle

The fixed front caster angle compensates for any camber option or seat angle without requiring adjustments to the front casters.



Adjustable Camber Tube & Plugs

The Quickie R2 models offer fully adjustable camber brackets that allow fast and easy center of gravity adjustments. With the adjustable camber plugs you can choose between single or dual camber without affecting the fixed front caster angle. Dual camber plugs accommodate camber changes without requiring front caster realignment.



Quickie® Rigid Series



Quickie Ti Titanium

LIGHTEST WEIGHT



Quickie XTR

SUSPENSION



Quickie R2 Adjustable

QUICK CAMBER ADJUSTMENT



Quickie R2 Rigid



Quickie ST/DT*

CHROME-MOLY FRAME



Quickie GPV Comp



Quickie GPV Ti

CLASSIC GP SERIES



Quickie GPV



Quickie GP SA

*Also available in ped. sizes.

Quickie Ti Titanium

Configuration Ranges		
Seat Width	13" - 18"	1" increments
Seat Depth	14" - 19"	1" increments
Front Frame Angle	70°, 80°, 85°	
Frame Inset	0", 1", 2"	
Titanium Backrest	10" - 15"	1" increments
Aluminum Backrest	11" - 20"	1" increments
Caster Sizes	3", 4", 5"	
Rear Wheels	24", 25", 26"	
Rear Wheel Spacing	0.75" - 1.5"	0.25" increments
Center of Gravity	0.5" - 4.5"	0.5" increments
Camber	0°, 2°, 4°, 8°	

Front Seat Height 0.5" increments	Rear Seat Height 0.5" increments	Footrest Adjustability Range (from sling - without cushion)
16	15" - 12.5"	13.25" - 11.25"
16.5	15.5" - 13"	13.75" - 11.75"
17	16" - 13.5"	14.25" - 11.25"
17.5	16.5" - 14"	14.75" - 11.75"
18	17" - 14.5"	15.25" - 12.25"
18.5	17.5" - 15"	15.75" - 12.75"
19	18" - 15.5"	16.25" - 13.25"
19.5	18.5" - 16"	16.75" - 13.75"
20	19" - 16.5"	17.25" - 14.25"

Quickie R2 Rigid/Quickie R2 Adjustable

FRONT SEAT HEIGHT						
CASTER OPTIONS	3" MICROS 3 ^{1/4} " FORK	3" MICROS 4 ^{1/4} " FORK	4" CASTERS 4 ^{3/4} " FORK	4" CASTERS 3 ^{1/4} " FORK	5" CASTERS 4 ^{3/4} " FORK	
Short	18"	18 ^{1/4} "	18 ^{1/4} "	18 ^{1/2} "	18 ^{1/2} "	
Regular	19"	19 ^{1/4} "	19 ^{1/4} "	19 ^{1/2} "	19 ^{1/2} "	
Tall	20"	20 ^{1/4} "	20 ^{1/4} "	20 ^{1/2} "	20 ^{1/2} "	

OVERALL CHAIR WIDTH	14"	15"	16"	17"	18"	19"	20"
SEAT WIDTH							
OVERALL CHAIR WIDTH- 3°	22 ^{1/4} "	23 ^{1/4} "	24 ^{1/4} "	25 ^{1/4} "	26 ^{1/4} "	27 ^{1/4} "	28 ^{1/4} "
OVERALL CHAIR WIDTH- 12°	28 ^{1/4} "	29 ^{1/4} "	30 ^{1/4} "	31 ^{1/4} "	32 ^{1/4} "	33 ^{1/4} "	34 ^{1/4} "

* sizes may vary 0/12 camber insert
WEIGHT: 22^{1/2} lbs. WEIGHT CAPACITY: 250 lbs.

Quickie XTR

	0 Degree Camber Tube		4 Degree Camber Tube		8 Degree Camber Tube*	
	Front Seat Height	Rear Seat Height	Front Seat Height	Rear Seat Height	Front Seat Height	Rear Seat Height
14" Depth	18 ^{3/4} "	17"	18 ^{3/4} "	16 ^{1/2} "	18 ^{3/4} "	16"
15" Depth	19"	17"	19"	16 ^{1/2} "	18 ^{3/4} "	16"
16" Depth	19"	17"	19"	16 ^{1/2} "	18 ^{3/4} "	16"
17" Depth	19 ^{1/4} "	17"	19 ^{1/4} "	16 ^{1/2} "	18 ^{3/4} "	16"
18" Depth	19 ^{1/4} "	17"	19 ^{1/4} "	16 ^{1/2} "	18 ^{3/4} "	16"

* with 8° camber, caster is mounted in upper hole set ** rounded to nearest 1/4"

FRAME WIDTH	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH	24"	25"	26"	27"	28"	29"	30"

* based on 0° camber
WEIGHT: 23^{1/2} lbs. WEIGHT CAPACITY: 250 lbs.

Quickie ST/DT

FRONT SEAT HEIGHT (Based on 5" caster / 24" rear wheel with 4° camber)					
STANDARD	SMALL STD	LARGE STD	STEEP	TALL	ULTRA TALL
19"	17 ^{1/2} "	20 ^{3/8} "	20"	20"	20"

REAR SEAT HEIGHT (Based on 5" caster / 24" rear wheel with 4° camber)					
STANDARD	SMALL STD	LARGE STD	STEEP	TALL	ULTRA TALL
15 ^{1/2} "	13 ^{7/8} "	16"	14 ^{1/2} "	17 ^{1/2} "	19 ^{3/4} "

FRAME WIDTH	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH	24"	25"	26"	27"	28"	29"	30"

* based on 0° camber
WEIGHT: 27 lbs. WEIGHT CAPACITY: 250 lbs.
* heights may vary 1/8"

*All specifications are subject to change with each configuration.

Quickie GPV

FRONT SEAT HEIGHT (For Standard Frames Only)					
CASTER OPTIONS	3" MICROS 6" FORK	5" LP POLY 5 ^{1/4} " FORK	6" PNEU 5 ^{1/4} " FORK	6" POLY 5 ^{1/4} " FORK	
CASTER FORK MOUNTING HOLE					
TOP	17 ^{3/8} "	17 ^{3/8} "	17 ^{3/4} "	17 ^{3/8} "	
BOTTOM	18 ^{3/8} "	18 ^{3/8} "	18 ^{3/4} "	18 ^{3/8} "	

REAR SEAT HEIGHT (For Standard Frames and Axle Position Only)								
REAR WHEEL	22" PNEU	24" LATEX TUBULAR	24" HP CLNCHR	24" PNEU	24" HT TEN/B-BALL TURBO TRD	26" LATEX/PNEU HP/CLNCHR	26" HT TEN/B-BALL TURBO TRD	26"
AXLE/HOLE POSITION								
TOP	15 ^{3/4} "	15 ^{7/8} "	16"	16 ^{1/8} "	16 ^{1/4} "	16 ^{3/8} "	17 ^{1/4} "	17 ^{5/8} "
MIDDLE	16"	16"	16 ^{3/8} "	16 ^{3/4} "	16 ^{7/8} "	17 ^{1/2} "	17 ^{3/8} "	18 ^{1/4} "
BOTTOM	16 ^{5/8} "	17 ^{1/8} "	17 ^{1/4} "	17 ^{3/8} "	17 ^{1/2} "	18 ^{1/8} "	18 ^{1/2} "	18 ^{7/8} "

FRAME WIDTH	12"	13"	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH (With Standard Camber No Armrests)	23"	24"	25"	26"	27"	28"	29"	30"	31"

WEIGHT: 21^{1/2} lbs. (w/steel rear axles)
19^{3/4} lbs. (w/titanium rear axles) WEIGHT CAPACITY: 250 lbs.

Quickie GPV Competition

FRONT SEAT HEIGHT (For Standard Frames Only)					
CASTER OPTIONS	3" MICROS 6" FORK	5" LP POLY 5 ^{1/4} " FORK			
CASTER FORK MOUNTING HOLE					
TOP	17 ^{7/8} "	17 ^{7/8} "	17 ^{15/16} "		
BOTTOM	18 ^{3/8} "	18 ^{3/8} "	18 ^{3/8} "		

REAR SEAT HEIGHT (For Standard Frames and Axle Position Only)							
REAR WHEEL	24" LATEX TUBULAR	24" HP CLNCHR	24" PNEU	24" HT TEN/B-BALL TURBO TRD	26" LATEX/PNEU HP/CLNCHR	26" HT TEN/B-BALL TURBO TRD	26"
AXLE/HOLE POSITION							
TOP	15 ^{7/8} "	16"	16 ^{1/8} "	16 ^{1/4} "	16 ^{3/8} "	17 ^{1/4} "	17 ^{5/8} "
MIDDLE	16"	16 ^{3/8} "	16 ^{3/4} "	16 ^{7/8} "	17 ^{1/2} "	17 ^{3/8} "	18 ^{1/4} "
BOTTOM	17 ^{1/8} "	17 ^{1/4} "	17 ^{3/8} "	17 ^{1/2} "	18 ^{1/8} "	18 ^{1/2} "	18 ^{7/8} "

FRAME WIDTH	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH (With Standard Camber No Armrests)	25"	26"	27"	28"	29"	30"	31"

WEIGHT: 21^{1/2} lbs. (w/steel rear axles)
19^{3/4} lbs. (w/titanium rear axles) WEIGHT CAPACITY: 250 lbs.

Quickie GP Swing-away

FRONT SEAT HEIGHT (For Standard Frames Only)					
CASTER OPTIONS	5" LP POLY 5 ^{1/4} " FORK	6" PNEU 5 ^{1/4} " FORK	6" POLY 5 ^{1/4} " FORK	8" POLY 5 ^{1/4} " FORK	
CASTER FORK MOUNTING HOLE					
TOP	15 ^{3/16} "	16 ^{1/8} "	16"	17 ^{1/8} "	
BOTTOM	16 ^{3/16} "	17 ^{1/8} "	17"	18 ^{1/8} "	

REAR SEAT HEIGHT (For Standard Frames and Axle Position Only)								
REAR WHEEL	22" PNEU	24" LATEX TUBULAR	24" HP CLNCHR	24" PNEU	24" HT TEN/B-BALL TURBO TRD	26" LATEX/PNEU HP/CLNCHR	26" PNEU	26" HT TEN/B-BALL TURBO TRD
AXLE/HOLE POSITION								
TOP	15 ^{7/8} "	16 ^{3/8} "	16 ^{1/2} "	16 ^{5/8} "	16 ^{3/4} "	17 ^{3/8} "	17 ^{3/4} "	18 ^{3/8} "
MIDDLE	16 ^{1/2} "	17"	17 ^{1/8} "	17 ^{1/4} "	17 ^{3/4} "	18"	18 ^{3/8} "	18 ^{1/4} "
BOTTOM	17 ^{1/8} "	17 ^{5/8} "	17 ^{3/4} "	17 ^{7/8} "	18"	18 ^{3/8} "	19"	19 ^{3/8} "

FRAME WIDTH	12"	13"	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH (With Standard Camber No Armrests)	22 ^{1/2} "	23 ^{1/2} "	24 ^{1/2} "	25 ^{1/2} "	26 ^{1/2} "	27 ^{1/2} "	28 ^{1/2} "	29 ^{1/2} "	30 ^{1/2} "

WEIGHT: 24^{1/2} lbs. WEIGHT CAPACITY: 250 lbs.

Quickie GPV Titanium

FRONT SEAT HEIGHT (For Standard Frames Only)					
CASTER OPTIONS	3" MICROS 6" FORK	5" LP POLY 6" FORK	6" PNEU 6" FORK	6" POLY 5 ^{1/4} " FORK	
CASTER FORK MOUNTING HOLE					
TOP	17 ^{7/8} "	18"	18 ^{15/16} "	18 ^{7/8} "	
BOTTOM	18 ^{3/8} "	19"	19 ^{15/16} "	19 ^{3/8} "	

REAR SEAT HEIGHT (For Standard Frames and Axle Position Only)								
REAR WHEEL	22" PNEU	24" LATEX TUBULAR	24" HP CLNCHR	24" PNEU	24" HT TEN/B-BALL TURBO TRD	26" LATEX/PNEU HP/CLNCHR	26" PNEU	26" HT TEN/B-BALL TURBO TRD
AXLE/HOLE POSITION								
TOP	15 ^{3/8} "	15 ^{7/8} "	16"	16 ^{1/8} "	16 ^{1/4} "	16 ^{3/8} "	17 ^{1/4} "	17 ^{5/8} "
MIDDLE	16"	16 ^{1/2} "	16 ^{5/8} "	16 ^{3/4} "	16 ^{7/8} "	17 ^{1/2} "	17 ^{3/8} "	18 ^{1/4} "
BOTTOM	16 ^{5/8} "	17 ^{1/8} "	17 ^{1/4} "	17 ^{3/8} "	17 ^{1/2} "	18 ^{1/8} "	18 ^{1/2} "	18 ^{7/8} "

FRAME WIDTH	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH (With Standard Camber and No Armrests)	25"	26"	27"	28"	29"	30"	31"

WEIGHT: 18 lbs. WEIGHT CAPACITY: 250 lbs.

For more information on the Quickie Rigid Series chairs and other products offered by Sunrise Medical visit:
www.sunrisemedical.com