he Quickie XTR "Xtreme Terrain Reflex" is the first monoshock suspension chair on the market. The Quickie XTR features Rock Shox®, a unique suspension system developed exclusively for Quickie. This system offers superior performance with factory-tuned rebound and compression, as well as better side to side stability. With the Quickie XTR the rider is assured a smooth, stable ride over a variety of terrain.



Mountain Tire Package

The Quickie XTR mountain tire package includes tires designed for a multitude of "xtreme" terrain. Both the heat treated and mountain tires are 24" in height, which make it easy to change wheels without having to re-adjust the chair.



Angle-adjustable Folding Backrest

The back and seat frames are attached together to facilitate seat-to-back angles and to accommodate posturing and positioning devices. The backrest can be folded completely for easy, compact transport.



Rock Shox® Monoshock Suspension

This unique suspension system provides a smoother ride up curbs and on uneven terrain, reducing back pain and fatigue. Rock Shox® has 2.5" rear wheel travel for shock absorption providing the rider with a more controlled and confident ride.





Quickie Ti Titanium

LIGHTEST WEIGHT



Quickie XTR SUSPENSION



Quickie R2 Adjustable Quickie R2 Rigid
QUICK CAMBER ADJUSTMENT



Quickie ST/DT*
CHROME-MOLY FRAME







Quickie GPV Quickie GP SA



*Also available in ped. sizes.

Quickie Ti Titanium

Quickle II IIIailiui	11		
Configuration Ranges			
Seat Width	13" - 18"	1" increments	
Seat Depth	14" - 19"	1" increments	
Front Frame Angle	70°. 80°. 85°		
Frame Inset	0", 1", 2"		
Titanium Backrest	10" - 15"	1" increments	
Aluminum Backrest	11" - 20"	1" increments	
Caster Sizes	3", 4", 5"	1 11101011101110	
Rear Wheels	24". 25". 26"		
Rear Wheel Spacing	0.75" - 1.5"	0.25" increments	
Center of Gravity	0.5" - 4.5"	0.5" increments	
Camber	0°, 2°, 4°, 8°		
Front Seat Height	Rear	Seat Height	Footrest Adjustability Range
0.5" increments		increments	(from sling– without cushion)
16		5" - 12.5"	13.25" - 11.25"
16.5"		5.5" - 13"	13.75" - 11.75"
17"		6" - 13.5"	14.25" - 11.25"
17.5"		6.5" - 14"	14.75" - 11.75"
18"		7" - 14.5"	15.25" - 12.25"
18.5" 19"		7.5" - 15" 8" - 15.5"	15.75" - 12.75" 16.25" - 13.25"
10.51		0 - 10.0	10.25 - 13.25

Quickie R2 Rigid/Quickie R2 Adjustable

	J		.,				
FRONT SEAT HEIGH	HT	O II MIODOO	OII MIO	DO0 4	. 0407500	4 0 A OTEDO	E II OAOTEDO
CASTER OPTIONS		3" MICROS 31/4" FORK	3" MIC 41/4"FO		" CASTERS 8/4" FORK	4" CASTERS 31/4" FORK	5" CASTERS 4 ^{3/4} "FORK
FRAME							
Short		18"	181/4"	18	31/4"	181/2"	181/2"
Regular		19"	191/4"	19	91/4"	191/2"	191/2"
Tall		20"	201/4"	20)1/4"	201/2"	201/2"
OVERALL CHAIR W SEAT WIDTH	/IDTH 14 "	15"	16"	17"	18"	19"	20"
OVERALL CHAIR WIDTH- 3°	223/4"	233/4"	243/4"	253/4"	263/4"	273/4"	283/4"
OVERALL CHAIR WIDTH- 12°	281/4"	291/4"	301/4"	311/4"	321/4"	331/4"	341/4"
* sizes may vary (0/12 camb	er insert					
WEIGHT: 221/2 lbs.					V	VEIGHT CAPACI	TY: 250 lbs
•							

Quickie XTR

	O Degree Ca Front Seat Height	mber Tube Rear Seat Height	4 Degree Ca Front Seat Height	amber Tube Rear Seat Height	8 Degree Ca Front Seat Height	mber Tube* Rear Seat Height	
14" Depth	183/4"	17"	183/4"	161/2"	181/4"	16"	
15" Depth	19"	17"	19"	161/2"	181/4"	16"	
16" Depth	19"	17"	19"	161/2"	181/211	16"	
17" Depth	191/4"	17"	191/4"	161/2"	181/2"	16"	
18" Depth * with 8° c		17" is mounted in	19 ^{1/4} " upper hole set	16 ^{1/2} " ** rounded t	18 ^{3/4} " o nearest 1/4"	16"	
FRAME WIDTH	14"	15"	16"	17"	18"	19"	20"
OVERALL WIDTH * based on	24" 0° camber	25"	26"	27"	28"	29"	30"
WEIGHT: 2	31/2 lbs.				WEIGHT CA	PACITY: 250	lbs.

Quickie ST/DT

LEICUT	(Donad on E" or	otor /2/1 room wh	ool with 10 or	mhor)						
,										
D	SMALL STD	LARGE STD	STEEP	TALL	ULTR/	TALL				
	171/2"	205/8"	20"	20"	20"					
REAR SEAT HEIGHT (Based on 5" caster /24" rear wheel with 4° camber)										
STANDARD SMALL STD		LARGE STD	STEEP	TALL	ULTR/	ULTRA TALL				
	137/8"	16"	141/2"	171/2"	193/4					
14"	15"	16"	17"	18"	19"	20"				
0.41	051	001	071	001	001	001				
		20	21	28	29	30"				
WEIGHT: 27 lbs. WEIGHT CAPACITY: 250 lbs.										
ay vary	1/8"									
	HEIGHT () 14" 24" 0° camb Ibs.	D SMALL STD 17 ^{1/2*} HEIGHT (Based on 5* cas D SMALL STD 13 ^{7/8*} 14* 15* 24* 25* 0° camber	SMALL STD	SMALL STD LARGE STD STEEP 17"2" 20"8" 20"	17' ^{12*} 20' ^{18*} 20' 20' HEIGHT (Based on 5" caster /24" rear wheel with 4° camber) D SMALL STD LARGE STD STEEP TALL 13' ^{18*} 16" 14' ^{12*} 17' ^{12*} 14* 15* 16* 17* 18* 24* 25* 26* 27* 28* 0° camber Ibs. WEIGHT CA	SMALL STD LARGE STD STEEP TALL ULTRA				

^{*}All specifications are subject to change with each configuration.

For more information on the Quickie Rigid Series chairs and other products offered by Sunrise Medical visit: www.sunrisemedical.com

Quickie GPV

FRONT SEAT HEIGHT (For Standard Frames Only)										
CASTER OPTIONS					5" LP POLY 6" PN 5"/4" FORK 5"/4"				POLY FORK	
CASTER FOR MOUNTING I TOP BOTTOM		17 ^{7/8} " 18 ^{7/8} "			17 ^{3/16} " 18 ^{3/16} "	17 ^{3/4} ' 18 ^{3/4} '			7 ^{5/8} " 8 ^{5/8} "	
REAR SEAT H REAR WHEEL	EIGHT (For 22" PNEU	Standard F 24" LATEX TUBULAR	rames and 24" HP CLNCHI		Position (24" PNEU	Only) 24" HT Ten/B-Ball Turbo Trd	26" LATEX/PI HP/CLNC	NEU	26" HT Ten/B-Ball Turbo t	
AXLE/HOLE POSITION TOP MIDDLE BOTTOM	15 ^{3/4} ** 16** 16 ^{5/8} **	15 ^{7/8} " 16" 17 ^{1/8} "	16" 16 ^{5/8} " 17 ^{1/4} "		16 ^{1/8} 16 ^{3/4} 17 ^{3/8}	16 ^{1/4} " 16 ^{7/8} " 17 ^{1/2} "	16 ^{7/8} 17 ^{1/2} 18 ^{1/8}		17 ^{1/4} " 17 ^{7/8} " 18 ^{1/2} "	17 ^{5/8} ** 18 ^{1/4} 18 ^{7/8} **
FRAME WIDTH	12"	13"	14"	15"	16"	17"	18"	19"	20	
OVERALL WIDTH	23" (With Star	24" ndard Cambe	25" er No Armr	26" ests)	27"	28"	29"	30"	31	
WEIGHT:		(w/steel rea (w/titanium		s)		WEIGHT C	APACITY:	250	lbs.	

Quickie GPV Competition										
FRONT SEAT I CASTER OPTIONS	#EIGHT (For Standard Frames Only) 3° MICROS 5° LP POLY 6° FORK 5°**FORK									
CASTER FORK MOUNTING HOLE TOP 17/78" 17 ^{2/16} " BOTTOM 18 ^{7/8} " 18 ^{2/16} "										
REAR SEAT H REAR WHEEL	EIGHT (For S 24" Latex Tubular	Standard Fram 24" HP CLNCHR	es and Axle 24" PNEU	Position On 24" HT TEN/B-BALL TURBO TRD	ly)	26" Latex/P HP/CLN		26" HT TEN/B-BALL TURBO TRD	26"	
AXLE/HOLE POSITION TOP MIDDLE BOTTOM	15 ^{7/8} * 16* 17 ^{1/8} *	16" 16 ^{5/8} " 17 ^{1/4} "	16 ^{1/8=} 16 ^{3/4=} 17 ^{3/8=}	16 ^{1/4} " 16 ^{7/8} " 17 ^{1/2} "		16 ^{7/8} " 17 ^{1/2} " 18 ^{1/8} "		17 ^{1/4} " 17 ^{7/8} " 18 ^{1/2} "	17 ^{5/8} " 18 ^{1/4} " 18 ^{7/8} "	
FRAME WIDTH	14"	15"	16"	17"	18"		19"	20"		
OVERALL WIDTH	25" (With Stand	26" lard Camber No	27" Armrests)	28"	29"		30"	31"		
WEIGHT:		v/steel rear av v/titanium rea					WEIGHT	CAPACITY:	250 lbs.	

Quickie GP Swing-away

QUICKIE	<u></u>		٠,								
FRONT SEAT	T HEIGHT	(For Stan	dard Fra	mes Only)							
CASTER OPTIONS			P POLY Fork	6" PNEU 51/4" FORK	6" POLY 51/4" FOR	8" POL K 5 ^{1/4} " FO					
CASTER FO											
TOP BOTTOM		15 ^{9/1} 16 ^{9/1}		16 ^{1/8} 17 ^{1/8}	16" 17"	17 ^{1/8} 18 ^{1/8}					
REAR SEAT REAR WHEEL	HEIGHT (F 22" PNEU	or Stand 24" LATE TUBL	(nes and Axle 24" HP CLNCHR	Position 0 24" PNEU	nly) 24" HT TEN/B-B TURBO T	ALL	26" LATEX HP/C	(/ LNCHR	26" PNEU	26" HT TEN/B-BALL TURBO TRD
AXLE/HOLI POSITION	E										
TOP MIDDLE BOTTOM	15 ^{7/8} " 16 ^{1/2} " 17 ^{1/8} "	16 ^{3/8} 17" 17 ^{5/8}		16 ^{1/2} ** 17 ^{1/8} ** 17 ^{3/4} **	16 ^{5/8} " 17 ^{1/4} " 17 ^{7/8} "	16 ^{3/4} " 17 ^{3/4} " 18"		17 ^{3/8} 18" 18 ^{5/8}		17 ^{3/4} " 18 ^{3/8} " 19"	18 ^{1/8} " 18 ^{3/4} " 19 ^{3/8} "
FRAME WIDTH	12"	13"	14"	15"	16"	17"	18"		19"		20"
OVERALL WIDTH	22 ^{1/2} " (With Star	23 ^{1/2} " ndard Can	24 ^{1/2} " nber No <i>i</i>	25 ^{1/2} " Armrests)	261/211	271/2"	281/2	211	291/2"		301/2"
WEIGHT:	241/2 lbs	8.			WEIGHT (APACITY:	250	lbs.			

Quickie GPV Titanium

FRONT SEAT I CASTER OPTIONS		CROS	nly) 5" LP POLY 6"FORK	6" PNEU 6" FORK	6" POL 5 ^{1/4} " FC			
CASTER FORI MOUNTING I TOP BOTTOM		17 ^{7/8} "		18" 19"	18 ^{9/16} "	18 ^{7/16} "		
REAR SEAT H REAR WHEEL	EIGHT (Fo 22" PNEU	r Standard F 24" LATEX TUBULAR	rames and 24" HP CLNCHR	d Axle Positio 24" PNEU	n Only) 24" HT TEN/B-BALL TURBO TRD	26" Latex/ HP/Clnchr	26" PNEU	26" TEN/B-BALL TURBO TRD
AXLE/HOLE POSITION TOP MIDDLE BOTTOM	15 ^{3/8} ** 16** 165/8**	15 ^{7/8} " 16 ^{1/2} " 17 ^{1/8} "	16" 16 ^{5/8} " 17 ^{1/4} "	16 ^{1/8} " 16 ^{3/4} " 17 ^{3/8} "	16 ^{1/4} " 16 ^{7/8} " 17 ^{1/2} "	16 ^{7/8} " 17 ^{1/2} " 18 ^{1/8} "	17 ^{1/4} " 17 ^{7/8} " 18 ^{1/2} "	17 ^{5/8} " 18 ^{1/4} " 18 ^{7/8} "
FRAME WIDTH	14"	15"	16"	17"	18"	19"	20'	
OVERALL WIDTH	25" (With Sta	26" Indard Camb	27" er and No	28" Armrests)	29"	30"	31"	
WEIGHT: 18 I	bs.				WEIGH	IT CAPACITY:	250 lbs	